F-Tool ZeroPoint Clamping System (ZPS)



simple palletising with the F-Tool PowerFlex Centring

Wonderfully simple...

F-Tool ZPS

The F-Tool ZPS is a simple, precise, powerful zero point clamping system. The positioning takes place by means of conically cut clamping pins which compress the centring ring during clamping and form a friction-locked connection with the base unit. This compensates for any lateral clearance. The pallet can be fastened to the ZPS base unit mechanically using screws or by means of an additional independent clamping mechanism.

FTool ZPS-300-36-M

- for standard-sized pallets 300 x 300 mm
- flat building height 36 mm
- strong screw connection for heavy weights and coarse chipping
- no air or hydraulics connection required
- no alignment pallet required




FTool ZPS-300-55-MP-MTS-Single

- for standard-sized pallets 300 x 300 mm and pallets Ø 148 mm
- central independent MTS clamping chuck for pallets PP148
- two clamping sizes in a (300 x 300 mm / Ø 148 mm)
- pallets can be clamped quickly and easily using air pressure
- In case of strong loads the pallets can also be secured with 4 x $^{\rm M12}$
- no alignment pallet required





F-Tool PowerFlex centring

The centring mechanism is wonderfully simple. The F-Tool PowerFlex centring ring can be inserted loosely in the prepared centring bore holes and fastened with the pre-centring plate.




Universal options of use









F-Tool ZeroPoint Clamping System (ZPS)




Universal

Precise


Flexible

Economical

In the FTool ZPS the four PowerFlex centring units automatically form a reference position in the centre of the base unit. The reference position is not as normally determined by a centring unit, but equalised evenly by means of the four PowerFlex centring rings. Minor deviations in the positioning on the pallet or thermal influence are systematically compensated and centrically distributed by the PowerFlex centring rings.



- 1 Pallet 300 x 300 mm
- (2) Clamping holes for M12
- (3) base plate
- (4) Integrated reference position
- (5) Integrated alignment edge
- 6 Fastening holes
- 7 Fastening slot
- (8) Clamping mechanism MTS
- (9) Air non-return valve



ZPS Technical Features


- simple components for flexible applications
- tolerant rough centring of +/- 5 mm to insert pallet
- short centring bolt, short paths (protruding only 14 mm)
- low installation height (PowerFlex centring unit t=12 mm)
- high positioning and repetition precision +/-0.005 mm means and devices
- for high loads and high lateral forces the pallets are fastened with $4 \times M12$ screws
- mechanical or pneumatic clamping/unclamping


ZPS possible applications


- manually or pneumatically operated palletizing system on processing centres
- positioning system in fixture construction
- multiple pick-up of machine tools
- fast changing system of clamping means and devices
- fast changing system on clamping cubes

Modular system for DIY

If necessary, the FTool PowerFlex centring can be arranged individually and as a double, quadruple or multiple palletizing system. The FTool PowerFlex centring is therefore also suitable for DIY positioning systems and devices. The low installation height of app. 20 mm opens up new palletizing options







| Article no. | Article | Quantity | Weight | Code | |
|-------------|--|-----------------|----------|------|--|
| FT 02160 | FTool ZPS-300-36-M manual basic unit | 1 piece | 26.00 kg | P | |
| FT 02161 | FTool ZPS-300-55-MP-MTS-single pneumatic basic unit (ER-033402) | 1 piece | | Р | |
| FT 02185 | FTool ZPS-300-55-MTS-MP Basic unit with pneumatic clamping (ER 033400) | 1 piece | | Р | |
| FT 02162 | FTool ZPS PowerFlex centring unit | Set of 2 pieces | 0.36 kg | Р | |
| FT 02163 | FTool pallet ER-PP148 alu (PowerPlate) (without spigot) | 1 piece | 1.41 kg | Р | |
| FT 02164 | FTool ZPS PowerFlex centering bolt | Set of 2 pieces | 0.20 kg | Р | |
| FT 02165 | FTool ZPS ALU pallet M 300 x 300 x 44 mm | 1 piece | 12.00 kg | Р | |
| FT 02166 | FTool ZPS pallet steel M 300 x 300 x 36 mm | 1 piece | 25.00 kg | Р | |
| FT 02167 | FTool ZPS ALU pallet MP 300 x 300 x 44 mm incl. MTS chucking spigot | 1 piece | 12.00 kg | P | |
| FT 02168 | FTool ZPS pallet steel MP 300 x 300 x 36 mm incl. MTS chucking spigot | 1 piece | 25.00 kg | Р | |